

Lingas de Correntes



MODELO	1 RAMAL	2 RAMAIS		3 E 4 RAMAIS	
	VERTICAL	0° À 45°	45° À 60°	0° À 45°	45° À 60°
	CAPACIDADE (Ton)	CAPACIDADE (Ton)	CAPACIDADE (Ton)	CAPACIDADE (Ton)	CAPACIDADE (Ton)
LINGA DE CORRENTE DE 6 mm	1,12	1,60	1,12	2,30	1,70
LINGA DE CORRENTE DE 8 mm	2,00	2,80	2,00	4,20	3,00
LINGA DE CORRENTE DE 10 mm	3,15	4,40	3,15	6,70	4,75
LINGA DE CORRENTE DE 13 mm	5,30	7,50	5,30	11,20	8,00
LINGA DE CORRENTE DE 16 mm	8,00	11,20	8,00	16,80	12,00
LINGA DE CORRENTE DE 18 mm	10,00	14,00	10,00	21,00	15,00
LINGA DE CORRENTE DE 20 mm	12,50	17,50	12,50	26,25	18,70
LINGA DE CORRENTE DE 22 mm	15,00	21,00	15,00	31,50	22,50
LINGA DE CORRENTE DE 26 mm	21,20	30,00	21,20	45,00	31,80

Opções de terminais



Clévis automático



Gancho clévis



Gancho olhal



Gancho automático



Encurtador de corrente