




Engrenagem 1.1/4" - ASA 100 - DIN 20B



Norma ASA
Correntes: ASA 100
Largura interna: 19,05
Ø do rolo: 19,05



Norma DIN
Correntes: DIN 20B
Largura interna: 19,56
Ø do rolo: 19,05



Nº DENTES z	Ø PRIM. (mm)	CÓDIGO	SIMPLES					DUPLA					
			FURO GUIA Ø A (mm)	FURO MÁX. Ø B (mm)	CUBO ØD (mm)	L (mm)	TIPOS	CÓDIGO	FURO GUIA Ø A (mm)	FURO MÁX. Ø B (mm)	CUBO ØD (mm)	L (mm)	TIPOS
11	112,70	110011	25	51	77	40	1,2,3	210011	25	51	77	70	1,2,3
12	122,67	110012	25	58	87	40	1,2,3	210012	25	58	87	70	1,2,3
13	132,67	110013	30	65	98	40	1,2,3	210013	30	65	98	70	1,2,3
14	142,68	110014	30	71	106	40	1,2,3	210014	30	71	106	70	1,2,3
15	152,71	110015	30	77	116	40	1,2,3	210015	30	77	116	70	1,2,3
16	162,74	110016	30	65	98	45	1,4,5	210016	30	65	98	75	1,4,5
17	172,79	110017	30	65	98	45	1,4,5	210017	30	65	98	75	1,4,5
18	182,84	110018	30	73	110	45	1,4,5	210018	30	73	110	75	1,4,5
19	192,90	110019	30	73	110	45	1,4,5	210019	30	73	110	75	1,4,5
20	202,96	110020	30	73	110	45	1,4,5	210020	30	73	110	75	1,4,5
21	213,03	110021	30	73	110	45	1,4,5	210021	30	73	110	75	1,4,5
22	223,10	110022	30	73	110	45	1,4,5	210022	30	73	110	75	1,4,5
23	233,17	110023	35	73	110	50	1,4,5	210023	35	73	110	75	1,4,5
24	243,25	110024	35	73	110	50	1,4,5	210024	35	73	110	75	1,4,5
25	253,33	110025	35	73	110	50	1,4,5	210025	35	73	110	75	1,4,5
28	283,57	110028	35	83	124	50	1,4,5	210028	35	83	124	75	1,4,5
30	303,75	110030	35	83	124	56	1,4,5	210030	35	83	124	75	1,4,5
35	354,20	110035	35	83	124	56	1,4,5	210035	35	83	124	75	1,4,5
38	384,48	110038	35	83	124	56	1,4,5	210038	35	83	124	75	1,4,5
38	384,48	110038	35	87	130	70	6	210038	35	87	130	80	6
40	404,67	110040	35	83	124	56	1,4,5	210040	35	83	124	80	1,4,5
45	455,16	110045	40	83	124	56	1,4,5	210045	40	83	124	80	1,4,5
45	455,16	110045	40	93	140	76	6	210045	40	93	140	85	6
48	458,45	110048	40	90	136	56	1,4,5	210048	40	90	136	80	1,4,5
54	546,05	110054	40	90	136	65	1,4,5	210054	40	90	136	80	1,4,5
57	576,35	110057	40	90	136	65	1,4,5	210057	40	90	136	80	1,4,5
57	576,35	110057	40	100	150	76	6	210057	40	100	150	85	6
76	768,30	110076	40	100	150	65	1,4,5	210076	40	100	150	80	1,4,5
76	768,30	110076	40	113	170	80	6	210076	40	113	170	90	6

